

### MCR-4V Specifications

Measurement Channels	Voltage 4ch
Input Method	Scanning Method, Differential Input, Each Channel Isolated
Input Impedance	Approx. 1.1 MΩ
Input Frequency	DC-100 Hz
Measurement Range	±300 mV, ±1.5 V, ±6 V, ±24 V, Auto (*1) Absolute Maximum Input Voltage: ±50 V
Accuracy	When the 50-60 Hz filter is ON, varies with the Measurement Range as follows: ±300 mV : ±(0.06 mV + 0.3% of reading) ±1.5 V : ±(0.3 mV + 0.3% of reading) ±6 V : ±(0.6 mV + 0.3% of reading) ±24 V : ±(2.4 mV + 0.3% of reading) Auto : According to the range in use
Measurement Resolution	50-60 Hz Filter ON : 0.01 mV 50-60 Hz Filter OFF : 0.1 mV
Recording Interval	2, 5, 10, 20, 50, 100, 200, 500 ms. / 1, 2, 5, 10, 15, 20, 30 sec. 1, 2, 5, 10, 15, 20, 30, 60 min. <input type="checkbox"/> The minimum interval will depend on the number of channels, measurement range, and 50-60 Hz filter setting.
Logging Capacity (*2)	When recording 1 channel : up to 480,000 readings/ch When recording 2 channels : up to 240,000 readings/ch When recording 3 channels : up to 160,000 readings/ch When recording 4 channels : up to 120,000 readings/ch
Recording Mode	Endless (Overwrite oldest data in the current recording session when capacity is full) or One Time (Stop recording when capacity is full)
Group Recording	Up to 4 units (16 channels) can be recorded simultaneously. Coupling of MCR-4V and MCR-4TC is possible. (*3)
LCD Display Items	Measurements, Trend Graph, Battery Level, etc.
Communication Interfaces	USB Communication
External Memory	SD Memory Card, SDHC Memory Card (*4) <input type="checkbox"/> For Manual or Automatic Data Export
Power	AA Alkaline Battery x 2, AA Ni-MH Battery x 2, AC Adaptor AD-05A2 or AD-05C2, USB Bus Power 5V 250mA
Battery Life (*5)	Approx. 4.5 to 130 days <input type="checkbox"/> 4 channels, Instantaneous value recording <input type="checkbox"/> With AA alkaline batteries
Input Terminal / Preheat Terminal	Screwless Terminals Compatible Wires Single Wire: φ 0.32 to φ 0.65 mm (AWG 28 - 22) Twisted Wire: 0.08 to 0.32 mm <sup>2</sup> (AWG 28 - 22), φ 0.12 mm or more in diameter Stripping Length : 9 to 10 mm
Isolation	CH1, CH2, CH3, CH4, USB, and Preheat are isolated. CH1-CH4 Maximum Applied Voltage : ±50 V Electrical Isolation Resistance : 50 MΩ or more (DC±250 V)
Dimensions	H 120 mm x W 75 mm x D 32 mm
Weight	Approx. 140 g
Operating Environment	Temperature: 0 to 50 °C Humidity: 90 %RH or less (no condensation)
Accessories	AA Alkaline Battery x 2, USB Mini-B Cable US-15C, Software CD-ROM, Card Slot Cover, User's Manual Set (Warranty Included)

- \*1: When "Auto" is selected, measurement range will be automatically changed according to the voltage being measured.  
\*2: If the logging capacity is not filled at the end of one recording session, the logger can record up to 30 times.  
\*3: Group Recording may not be started depending on the recording or measurement interval specifications of the connected Master unit.  
\*4: Please check the T&D Website for information on memory cards whose operation has been confirmed.  
\*5: Battery life varies depending upon multiple factors including measurement interval and 50-60 Hz filter setting. All estimates are based on operations carried out with a new battery and are in no way a guarantee of actual battery life.

### Software (MCR for Windows)

Compatible OS (*1)	Microsoft Windows 10 32 / 64 bit Microsoft Windows 8 32 / 64 bit Microsoft Windows 7 32 / 64 bit
Display Languages (*2)	English
Other	The Microsoft .NET Framework 4 is required.

- \*1: For installation, it is necessary to have Administrator ( Computer Administrator ) rights.  
\*2: We recommend using an operating system in the same language as the display language. Operation in different languages is not guaranteed.

### MCR-4TC Specifications

Measurement Channels	Temperature 4ch																				
Input Method	Scanning Method, Differential Input, Each Channel Isolated																				
Compatible Sensors	Thermocouple: Type K, J, T, S, R																				
Measurement Units	°C, °F																				
Measurement Range	Type K : -270 to 1370 °C      Type S : -50 to 1760 °C Type J : -210 to 1200 °C      Type R : -50 to 1760 °C Type T : -270 to 400 °C																				
Input Impedance	Approx. 1 MΩ																				
Accuracy (*1)	Thermocouple Measurement (Sensor inaccuracies not included) Type K, J, T : ±(0.5 °C + 0.3 % of reading) at -100°C or above Type S, R : ±(1.5 °C + 0.3 % of reading) at 100°C or above Cold Junction Compensation ±0.5°C at 10 to 40 °C ±0.8°C other temperatures within the operating environment of the logger																				
Measurement Resolution	0.1 °C																				
Recording Interval	100, 200, 500 ms. / 1, 2, 5, 10, 15, 20, 30 sec. 1, 2, 5, 10, 15, 20, 30, 60 min.																				
Logging Capacity (*2)	When recording 1 channel : up to 960,000 readings/ch When recording 2 channels : up to 480,000 readings/ch When recording 3 channels : up to 320,000 readings/ch When recording 4 channels : up to 240,000 readings/ch																				
Recording Mode	Endless (Overwrite oldest data in the current recording session when capacity is full) or One Time (Stop recording when capacity is full)																				
Group Recording	Up to 4 units (16 channels) can be recorded simultaneously. Coupling of MCR-4TC and MCR-4V is possible. (*3)																				
LCD Display Items	Measurements, Trend Graph, Battery Level, etc.																				
Communication Interfaces	USB Communication																				
External Memory	SD Memory Card, SDHC Memory Card (*4) For Manual or Automatic Data Export																				
Power	AA Alkaline Battery x 2, AA Ni-MH Battery x 2, AC Adaptor AD-05A2 or AD-05C2, USB Bus Power 5V 250mA																				
Battery Life (*5)	For 4-Channel Measurement (AA Alkaline Battery)																				
	<table border="1"> <thead> <tr> <th>Rec.Interval</th> <th>Rec.Method</th> <th>Instantaneous Value</th> <th>Average Value</th> </tr> </thead> <tbody> <tr> <td>100 ms</td> <td></td> <td>Approx. 5 days</td> <td>Approx. 5 days</td> </tr> <tr> <td>500 ms</td> <td></td> <td>Approx. 7 days</td> <td>Approx. 7 days</td> </tr> <tr> <td>1 sec</td> <td></td> <td>Approx. 21 days</td> <td>Approx. 7 days</td> </tr> <tr> <td>5 sec or longer</td> <td></td> <td>Approx. 60 days</td> <td>Approx. 21 days</td> </tr> </tbody> </table>	Rec.Interval	Rec.Method	Instantaneous Value	Average Value	100 ms		Approx. 5 days	Approx. 5 days	500 ms		Approx. 7 days	Approx. 7 days	1 sec		Approx. 21 days	Approx. 7 days	5 sec or longer		Approx. 60 days	Approx. 21 days
Rec.Interval	Rec.Method	Instantaneous Value	Average Value																		
100 ms		Approx. 5 days	Approx. 5 days																		
500 ms		Approx. 7 days	Approx. 7 days																		
1 sec		Approx. 21 days	Approx. 7 days																		
5 sec or longer		Approx. 60 days	Approx. 21 days																		
Input Terminal	Screwless Terminals Compatible Wires Single Wire : φ 0.32 to φ 0.65 mm (AWG 28 - 22) Twisted Wire : 0.08 to 0.32 mm <sup>2</sup> (AWG 28 - 22), φ 0.12 mm or more in diameter Stripping Length : 9 to 10 mm																				
Isolation	CH1, CH2, CH3, CH4, and USB are isolated. CH1-CH4 Maximum Applied Voltage : ±50 V Electrical Isolation Resistance : 50 MΩ or more (DC±250 V)																				
Dimensions	H 120 mm x W 75 mm x D 32 mm																				
Weight	Approx. 140 g																				
Operating Environment	Temperature: 0 to 50 °C Humidity: 90 %RH or less (no condensation)																				
Accessories	AA Alkaline Battery x 2, USB Mini-B Cable US-15C, Software CD-ROM, Card Slot Cover, User's Manual Set (Warranty Included)																				

- \*1: MCR-4TC has superior noise filter, but the measurement may sometimes fluctuate due to strong noise. Especially when the recording interval is set to 200 ms or less, the filtering becomes weaker and hence the fluctuation may become greater.  
\*2: If the logging capacity is not filled at the end of one recording session, the logger can record up to 30 times.  
\*3: Group Recording may not be started depending on the recording or measurement interval specifications of the connected Master unit.  
\*4: Please check the T&D Website for information on memory cards whose operation has been confirmed.  
\*5: Battery life varies depending upon multiple factors including ambient temperature, recording interval, number of measurement channels, and frequency of data export to a memory card. All estimates are based on operations carried out with a new battery and are in no way a guarantee of actual battery life.

- Colors in the photos in this catalog may be different from real product colors.
- The specification and designs of the products in this catalog are true as of 08.2019 Specifications are subject to change without notice.
- Microsoft and Windows are registered trademarks of Microsoft Corporation USA and other countries.
- Company names and product names are trademarks or registered trademarks of each company.
- The specifications listed above are subject to change without notice.

## T&D Corporation

817-1 Shimadachi, Matsumoto, Nagano 390-0852, Japan  
Please send your inquiries to:  
E-mail : sales@tannd.com  
Facsimile : (+81) 263-40-3152



2019.08.16304820007D (4th Edition)

# Multichannel Recorder

# MCR-4V/4TC

Voltage / Temperature (Thermocouple)






# 4-Channel Battery Operated Data Loggers Up to 16 Channels of Simultaneous Recording

Easy Connection of MCR-4V and MCR-4TC for Synchronous Measurement of Voltage and Temperature

Trend Graph for Real-Time Data Check



Easy Touch Panel Operation

Large Capacity Internal Memory

MCR-4V: Data logging up to 480,000 readings  
MCR-4TC: Data logging up to 960,000 readings

Electrical Isolation between Channels

MCR-4V: Capable of measuring signals of different potentials  
MCR-4TC: Possible to directly connect the exposed thermocouple junction to the measured object


Runs on 2 AA Alkaline Batteries or USB Bus Power

SD Memory Cards for Long-Period Recording

When coupling units, please prepare a memory card for each unit.

## MCR-4V Features

Preheat Function for Saving Battery Power




Quick and Precise Measurements Recording Interval as short as 2 msec / Resolution of 10 $\mu$ V

Number of Channels	Shortest Possible Recording Interval
1 ch	2 msec
2 ch	5 msec
4 ch	10 msec

- Number of channels determines shortest possible recording interval.
- Two recording methods: instantaneous value or average value.


Scale and Unit Conversion for Recording and Viewing



## MCR-4TC Features

Support for Variety of Thermocouple Types (K, J, T, S, R)


Wide Measurement Range from -270 to 1760 $^{\circ}$ C (varies with sensor type)



## Application Examples


### MCR-4V

- Measure and record data for control devices and measurement instruments in factories
- Record signals from actinometers, anemoscopes and CO<sub>2</sub> meters
- Record output signals from a variety of sensors and analyzers
- Measure voltage in electrical circuits



### MCR-4TC

- Record temperatures in pipes and ducts
- Record boiler temperatures
- Record temperatures in cooking equipment such as pans, fryers, and ovens
- For temperature management of refrigerated and frozen goods



### MCR-4V and MCR-4TC

- For temperature and pressure measurements inside slow cookers, pressure cookers, or other enclosed cooking containers.
- Measure air-conditioner gas pressure and outlet air temperature
- For measurement of engine combustion pressure and water cooling temperature.

## T&D Graph: High Performance Graph Tool

- View recorded data in colorful graph form as well as analyze data using generated cumulative values, highest, lowest, and average readings.
- Add comments and memos directly to graphs.
- Save data in CSV text format for use with spreadsheet software.

